

### Product Description


- **Dimensions** Size plank 914,4 x 152,4 x 5,3 mm
- **Packaging** Planks / box = 15 = 2,09 m<sup>2</sup> (16,43 kg)  
Boxes / pallet = 63 = 131,67 m<sup>2</sup> (1057 kg)
- **Composition**
  1. Top coating, made of polyurethane
  2. Wear layer with printed design film underneath
  3. Solid PVC backing
  4. Unique HIPS (High Impact polystyrene) click frame
  5. Acoustic dampening backing
- **Features** Micro V bevel on 4 sides
- **Click system** Glueless revolutionary mechanical locking system
- **Installation** see box / [www.dreamclick.be](http://www.dreamclick.be)

Size plank 36" x 6" x 0.20"

Planks / box = 15 = 22.49 sq ft (36.81lb)

Boxes / pallet = 63 = 1,416.87 sq ft (2,354 lb)


Tile and plank construction:



### Requirements

Classification Requirements class 23/33/42

Characteristics	Method	Value
Total thickness	EN 428	5,30 mm/.20 inches
Wear layer	EN 429	055 mm/ 22 MIL
Total weight	EN 430	8 kg/m <sup>2</sup> (.5lbs/ft <sup>2</sup> )
Surface treatment		PUR
Usage classification	EN 685	23 - 33 - 42
Underfloor heating	EN 12524	suitable - max. 27°
Castor chair	EN 425	pass
Fire resistance	EN 13501-1	Bfl-s1
Slip resistance	DIN 51130	R 10
	EN 13983	class DS
Sound reduction	EN ISO 717-2 (Lw)	8 dB
Light fastness	ISO 105-B02	> 6
Drum noise	EPLF	SL60
Locking strength		500 kg/m
Anti static	EN 1815	yes
Formaldehyde emission	EN 717-1	E1
Chemical resistance	EN 423	OK
Residual indentation warranty (Res / Com)	EN 433	< 0,10 mm lifetime/ 10 years



### Warranty and maintenance

- Residential warranty: Lifetime, commercial warranty: 10 years
- Warranty conditions, care and maintenance: see [www.berryalloc.com](http://www.berryalloc.com)

